

Rubinetti / Taps

**MEMORY**
**IMEM325NZS**

PARTE INCASSO PER VASCA DA TERRA

BUILT-IN PART FOR FLOOR MOUNTED BATHTUB TAP



Prima di realizzare l'impianto  
consultare la scheda Cod. 16024 .


Before installing consult the technical  
sheet cod. 16024

MINIMUM PRESSURE	1 BAR
MAXIMUM PRESSURE	5 BAR
RECCOMENDED WORKING PRESSURE	2-3 BAR
MAX. WATER TEMPERATURE	65°C 149°F
MAXIMUM WATER TEMPERATURE RECCOMENDED	65°C 149°F
MAXIMUM IN-LET PRESSURE DIFFERENCE (HOT-COLD)	1,5 BAR


Installation must comply with the Plumbing Code of Australia and AS/NZS 3500 series

If applicable, any flow control aerator installed in the product must be tightened to prevent removal by hand


CONTENUTO DELLA CONFEZIONE  
PACKAGE CONTENTS





INCASSO-BUILT-IN PART  
IMEM325NZS



STRUMENTI  
TOOLS




IMEM325NZS



FIL. G1/2  
HOT WATER

FIL. G1/2  
COLD WATER




1

Minimo livello di incasso  
Minimum level for built-in part

FILO PAVIMENTO FINITO  
FLUSH WITH THE FINISHED FLOOR



MIN. 82.5(3" 1/4)  
MAX. 102.5(4" 1/32)



2


Spurgo tubazioni  
Purge the pipes

15s



calda/hot

fredda/cold




calda/hot

fredda/cold

3

Punta Ø6  
Drill Bit Ø6



4

