

Rubinetti / Taps

MEMORY
IMEM327NZZ

Incasso bocca da terra

Built-in part of floor standing spout



Prima di realizzare l'impianto consultare la scheda Cod. 16024 .


Before installing the system refer to the Code tab. 16024 .

MINIMUM PRESSURE	1 BAR
MAXIMUM PRESSURE	5 BAR
RECOMMENDED WORKING PRESSURE	2-3 BAR
MAX. WATER TEMPERATURE	65°C 149°F
MAXIMUM WATER TEMPERATURE RECOMMENDED	65°C 149°F
MAXIMUM IN-LET PRESSURE DIFFERENCE (HOT-COLD)	1,5 BAR


Installation must comply with the Plumbing Code of Australia and AS/NZS 3500 series

If applicable, any flow control aerator installed in the product must be tightened to prevent removal by hand



CONTENUTO DELLA CONFEZIONE
PACKAGE CONTENTS









INCASSO-BUILT-IN PART
IMEM327



STRUMENTI
TOOLS




IMEM337NZS



1


Minimo livello di incasso
Minimum level for built-in part

filo pavimento
flush with the finished floor




2


Surgo tubazioni
Purge the pipes



3




4




5


Punta Ø6
Drill bit Ø6



6




7





8

VITI DI REGOLAZIONE
ADJUSTMENT SCREW





VITE DI FISSAGGIO
FIXING SCREW

9




10



11

MURATURA
MASONRY



12

